

FLUX



CENTRIFUGAL DUCT FANS






| MODELS | PROTECTION | m ³ /h | l/s | dB(A)* | Pa | W |
|----------------------|------------|-------------------|-------|--------|---------|-------|
| FLUX 100 | IPX4 | 90 | 25 | 44 | 128 | 30 |
| FLUX 250/100 | IPX4 | 210 | 58 | 52 | 220 | 50 |
| FLUX 250/120 | IPX4 | 240 | 67 | 52 | 220 | 50 |
| FLUX 100 2 speed | IPX4 | 90/38 | 25/11 | 44/37 | 128/75 | 30/12 |
| FLUX 250/100 2 speed | IPX4 | 240/110 | 67/31 | 52/41 | 220/110 | 50/23 |
| FLUX 250/120 2 speed | IPX4 | 240/128 | 67/36 | 52/41 | 220/110 | 50/23 |

* at 3 m - 230V/50Hz

Back draught shutter, removable filter and anti-vibration gasket as standard.

Versions

-  Integral adjustable timer
-  MHT humidity control
-  Pull cord switch

| DIMENSIONS (mm) | | | | | | |
|-----------------|-----|-----|-----|-----|----|-----|
| MODELS | A | B | C | D | F | ØE |
| FLUX 100 | 160 | 160 | 119 | 89 | 30 | 97 |
| FLUX 250/100 | 210 | 210 | 156 | 131 | 25 | 97 |
| FLUX 250/120 | 210 | 210 | 156 | 131 | 25 | 119 |

